


HEBEL PANELS



▲ TOP OF BORED PIER / NATURAL GROUND (REFER TO SCHEDULE)

CSR HEBEL NOISE WALL INSTALLATION SAFE

WORK METHOD STATEMENT:

1. WELD THE 300mm LONG, 150x90x8 UA HORIZONTALLY ONTO THE VERTICAL STEEL POST AT THE REQUIRED LEVEL.
2. PROVIDE LEVELLING GROUT AS PER THE STRUCTURAL DETAILS.
3. LOWER THE FIRST HORIZONTAL PANEL SLOWLY INTO THE GROUT, SQUASHING THE GROUT SO IT FILLS THE HEBEL PANEL'S GROOVE AND Voids AND ENSURES FULL CONTACT IS ACHIEVED BETWEEN THE PANEL AND THE ANGLE. THE LOWERING SHOULD BE STOPPED WHEN THE PANEL IS LEVEL AND A MINIMUM 10mm GROUT THICKNESS IS REACHED.
4. ALLOW THE GROUT TO CURE BEFORE INSTALLING THE SUBSEQUENT HORIZONTAL PANELS ABOVE.

ISSUE	NOTES	DATE
A	PRELIMINARY ISSUE	03/08/09

<p>CSR PANEL SYSTEMS Level 3 9 HEBEL STREET CHATSWOOD NSW 2067</p> <p>Phone: (02) 9235 8000 Fax: (02) 9372 5453 A.B.N. 55 008 631 356</p>	<p>CLIENT</p> <p>The better way to build CSR Building Products Limited 112 Wisemans Ferry Road Somersby, NSW 2300 Phone: (02) 4340 3380 Fax: (02) 4340 3300</p>																		
	<p>PROJECT</p> <p>CSR STANDARD SOUND BARRIER</p>																		
<p>DRAWING TITLE</p> <p>TYPICAL SOUND BARRIER SUPPORT DETAIL - OPTION 2</p>	<table border="1"> <tr> <td>NUMBER IN SET</td> <td>JOB NO</td> <td>SAMPLE</td> </tr> <tr> <td>SCALE</td> <td>SHEET NUMBER</td> <td>TEM-05</td> </tr> <tr> <td>DESIGN</td> <td>CHECK</td> <td>REV</td> </tr> <tr> <td>PM</td> <td>DD</td> <td>A</td> </tr> <tr> <td>DRAWN</td> <td>DATE</td> <td>03/08/09</td> </tr> <tr> <td>VC</td> <td> </td> <td> </td> </tr> </table>	NUMBER IN SET	JOB NO	SAMPLE	SCALE	SHEET NUMBER	TEM-05	DESIGN	CHECK	REV	PM	DD	A	DRAWN	DATE	03/08/09	VC		
NUMBER IN SET	JOB NO	SAMPLE																	
SCALE	SHEET NUMBER	TEM-05																	
DESIGN	CHECK	REV																	
PM	DD	A																	
DRAWN	DATE	03/08/09																	
VC																			